

County Surveyor's Record, Douglas County, Oregon

48

Subdivisions of T. 32 S., R. 9 W.

CHAINS

from which

A fir, 18 ins. diam., bears N.68\*E., 31 lks. dist.,  
marked 1/2 S 9 B T.

A fir, 30 ins. diam., bears N.70\*W., 40 lks. dist.,  
marked 1/2 S 8 B T.

- 40.50 Top of spur, slopes E.
- 43.10 Creek, 1 lk. wide, course E.
- 45.95 Creek, 2 lks. wide, course SE.
- 48.00 Enter burn, bears E. and W.
- 59.00 Top of spur, slopes E.
- 60.50 Leave burn, bears E. and W.
- 64.70 Ravine, course E.
- 68.60 Top of spur, slopes E.
- 72.20 Ravine, course E.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 4, 5, 8 and 9, with brass cap  
marked

T32S	R9W
S5	S4
S8	S9
1917	

from which

A fir, 16 ins. diam., bears N.47\*E., 16 lks. diam.,  
marked T 32 S R 9 W S 4 B T.

A chinquapin, 14 ins. diam., bears S.31\*E., 12 lks.  
dist., marked T 32 S R 9 W S 9 B T.

A fir, 40 ins. diam., bears S.10\*W., 41 lks. dist.,  
marked T 32 S R 9 W S 8 B T.

A fir, 20 ins. diam., bears N.74\*W., 41 lks. dist.,  
marked T 32 S R 9 W S 5 B T.

Land, mountainous.

Soil, gravelly clay loam, 2nd rate.

Timber, fir, sugar pine, chinquapin and cedar.

Undergrowth, rhododendron, tan oak, chinquapin and fir.

S.89\*57'E., on a random line, bet. secs. 4 and 9.

- 40.00 Set temp. 1/4 sec. cor.