


County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 32 S., R. 9 W.

CHAINS

30.19 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked



from which

A fir, 36 ins. diam., bears S.62\*E., 41 lks. dist., marked  $\frac{1}{4}$  S 4 B T.

A fir, 36 ins. diam., bears N24\*W., 32 lks. dist., marked  $\frac{1}{4}$  S 5 B T.

40.25 Top of spur, slopes E.

43.70 Ravine, course E.

48.40 Top of spur, slopes NE.

50.80 Ravine, course E.

53.40 Ravine, course NE.

58.50 Dry bed of creek, 4 lks. wide, course NE.; ascend.

70.19 The cor. of secs. 4, 5, 8 and 9.

Land, mountainous.


Soil, stony clay loam, 2nd and 3rd rate.

Timber, cedar, chinquapin and laurel.

Undergrowth, rhododendron, tan oak and chinquapin.

N.0\*03\*W., bet. secs. 19 and 20.\*\*\*\*\*

80.00 Set an iron post, 3 ft. long, 2 ins diam., 24 ins. in the ground, for cor. of secs. 17, 18, 19 and 20, with brass cap marked



from which

A chinquapin, 10 ins diam., bears N.21\*E., 34 lks. dist., marked T 32 S R 9 W S 17 B T.

A chinquapin, 14 ins. diam., bears S.33\*E., 20 lks. dist., marked T 32 S R 9 W S 20 B T.