

County Surveyor's Record, Douglas County, Oregon

Exteriors of T. 33 S., R. 4 W.

CHAINS	
50.00	A large spring of pure cold water, bears West 1.00 chs.
59.50	Head of spring, bears NW.
64.65	Spring brook 1 lk. wide, course NW.
75.00	Top of bluff, 50 ft. high.
	Va. 21*30'E
77.50	The Va. now is 19*15'E.
79.50	Spring branch, 2 lks. wide, course NW.
80.00	300 ft. below summit of main divide. Set a basaltic stone 24 x 16 x 14 ins., 18 ins. in the ground, for cor. to secs. 7, 12, 13 and 18, marked with 4 notches on S. sides and 2 notches on N. side, from which A Fir, 24 ins. diam., bears N.56*E., 31 lks. dist., marked T 33 S R 4 W S 7 B T. A W. Fir, 10 ins. diam., bears S.41*E., 32 lks. dist., marked T 33 S R 4 W S 18 B T. A Cedar, 16 ins. diam., bears S.12*W., 30 lks. dist., marked T 33 S R 5 W S 13 B T. A W. Fir, 18 ins. diam., bears N.15*W., 31 lks. dist., marked T 33 S R 5 W S 12 B T. Land mountainous, broken, rough, high, sloping to the N. Soil, gravelly, rocky, 4th rate. Heavy timber, Fir, Pine, Cedar, 71.00 chs. Dense undergrowth, Manzanita and Hazel, 80.00 chs. September 14, 1893.
	North, between secs. 7 and 12.
	Va. 19*E
	Descend mountain on NW. slope.
17.00	Ravine, bears NW.
20.00	A Fir, 3 ft. diam., on line, marked with 2 notches on N. and S. sides.
24.50	Mountain spur, bears NW.
32.50	Mountain spur, bears NW.
40.00	Set basaltic stone, 18 x 10 x 12 ins., 12 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face, from which