

County Surveyor's Record, Douglas County, Oregon

Exteriors of T. 33 S., R. 4 W.

CHAINS

General Description

5 miles and 75.00 chs. of the township lines run over mountain land or through heavy timber or dense undergrowth.

This entire township line runs over a mountainous rough, broken country, gravelly rocky soil, averaging not better than 3rd rate, through heavy timber and dense underbrush.

The highest point reached was between secs. 13 and 18 on Onion Spring mountain and is reported to be 5000 ft. above the level of the sea. It is difficult to approximate elevations as smoke or forrest conceal the topography and the hardships in ascending are deceptive to the ease in descending. The notes are as close as possible.

Subdivisions of T. 33 S., R. 4 W.
Same Deputies and Contract.

North, 2'W., between secs 9 and 10.*****

80.00

Set a post 4 ft. long, 4 ins. sq., 24 ins. in the ground for cor. to secs. 3, 4, 9 and 10, marked T 33 S S 3 on NE.. R 4 W S 10 on SE. S 9 on SW and S 4 on NW. faces with 5 notches on S; and 3 notches on E edge, from which

A Fir, 12 ins. diam., bears N.51*E., 39 lks. dist., marked T 33 S R 4 W S 3 B T.

A Fir, 11 ins. diam., bears S.31*E., 35 lks. dist., marked T 33 S R 4 W S 10 B T.

A Fir, 10 ins. diam., bears S.86*W., 73 lks. dist., marked T 33 S R 4 W S 9 B T.

A Fir, 36 ins. diam., bears N.35*W., 44 lks. dist., marked T 33 S R 4 W S 4 B T.

Land, mountainous, broken, rough,