

Subdivisions of T. 33 S., R 4 W.

CHAINS

point for closing cor.

Thence I run

West on 7th Standard Parallel.

Va20*E

Descend on W. slope 200 ft. to

7.00 Foot of descent and canyon, bears South.

Ascend mountain 350 ft. to

16.00 The Standard 1/4 sec. cor., which is a post 12 ins. above ground, marked S C 1/4 S on N. face, from which

A Fir, 12 ins. diam., bears S.50*W., 25 lks. dist., with well defined blazes.

A Fir, 6 ins. diam., bears N.45*W., 6 lks. dist., with well defined blazes.

I returned to my point of intersection, for closing cor. to secs. 3 and 4, which would be 16.00 chs. less 40.00 chs. or 24.00 chs. West of 7th Standard cor. to secs. 33 and 34 T 32 S R 4 W with N. boundary of Tp. and for closing cor. to secs. 3 and 4 I set a basaltic stone, 14 x 10 x 12 ins., 10 ins. in the ground, marked CAC with 3 notches on E. and W. edges, from which

A Fir, 12 ins. diam., bears S.63*15'E., 137 lks. dist., marked T 33 S R 4 W S 3 B T.

A Fir, 4 ft. diam., bears S.89*W., 80 lk. dist., marked T 33 S R 4 W S 4 B T.

A Fir, 12 ins. diam., bears N.55*30'E., 111 lks. dist., marked T 33 S R 4 W C C S 3 and 4 B T.

This cor. is 300 ft. above creek at 42.53 chs.

Land, mountainous, broken, rough.

Soil, gravelly with rock. 4th rate.

Heavy timber of Fir and Cedar.

Dense underbrush, Chinquapin and small Fir, 74.70 chs.

September 6 1893.