

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 33 S., R. 4 W.

CHAINS

North, 3'W., between secs. 16 and 17.*****

- 80.00 Set a basaltic stone 18 x 10 x 10 ins. 12 ins., in the ground, for cor. to secs. 8, 9, 16 and 17, marked with 4 notches on S. and E. edges, from which
- A Cedar, 18 ins. diam., bears N.60*E., 30 lks. dist., marked T 33 S R 4 W S 9 B T .
- A Cedar, 14 ins. diam., bears S.35*E., 30 lks. dist., marked T 33 S R 4 W S 16 B T .
- A Fir, 12 ins. diam., bears S.71*W., 43 lks. dist., marked T 33 S R 4 W S 17 B T .
- A Cedar, 16 ins. diam., bears N.21*W., 43 lks. dist., marked T 33 S R 4 W S 8 B T .

Land, mountainous, broken, rough, high.

Soil. gravelly, rocky, 4th rate.

Heavy timber, Fir, Cedar and Pine.

Dense underbrush, small Fir, Live Oak, Yew, Hazel and Vine Maple, 80.00 chs.

September 10, 1893.

North, 3'W., between secs. 8 and 9.

Va. 17*30'E

Descend mountain, 40 ft. to

- 1.50 Foot of descent and spring branch, 2 lks. wide, bears E.

Ascend mountain on E. slope.

- 6.20 Fir, 3 ft. diam., on line, marked with 2 notches on N. and S. sides.

- 24.40 A W. Fir, 20 ins. diam., on line, marked with 2 notches on N. and S. sides.

- 34.00 A Fir, 4 ft. diam., on line, marked with 2 notches on N. and S. sides.

- 40.00 Set basaltic stone, 18 x 10 x 6 ins. 12 ins. in the ground, marked $\frac{1}{4}$ on W. face, from which

A Fir, 2 ft. diam., bears N.50*E., 26 lks. dist., marked $\frac{1}{4}$ S B T.

A Cedar, 12 ins. diam., bears S.21*W., 11 lks. dist., marked $\frac{1}{4}$ S B T .