

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 33 S., R 4 W.

CHAINS	
	Ascend gradually along S. slope to creek.
13.10	Creek, 3 lks. wide, course S.70*E.
	Ascend mountain on NE. slope.
35.00	Ravine, 50 ft. deep, bears SE.
40.10	Set basaltic stone 14 x 8 x 6 ins. 10 ins. in the ground, marked $\frac{1}{4}$ on N. face, from which A Fir, 16 ins. diam., bears N.50*E., 44 lks. dist., marked $\frac{1}{4}$ S B T. A Fir, 20 ins. diam., bears S.40*W., 44 lks. dist., marked $\frac{1}{4}$ S B T.
51.00	Summit of mountain divide, bears N. and S. 800 ft. above cor. to secs. 3, 4, 9 and 10. Descend on W. slope.
52.25	Trail, bears N. and S.
55.75	Ravine, 40 ft. below divide, bears N. and S. Ascend, 300 ft.
59.00	A Fir, 2 ft. diam., on line, marked with 2 notches on E. and W. sides.
80.20	The cor. to secs. 4, 5, 8 and 9. Land, mountainous, broken, rough, high. Soil, gravelly, rocky, 4th rate. Heavy timber, Fir, Pine, Cedar. Dense underbrush, Mountain Laurel and small Fir, 80.20 chs. September 11, 1893.
	North, 3'W., between secs. 4 and 5. Va. 17*30'E
	Ascend gradually, 15 ft. to
4.00	Top of ascent. Descend mountain on N. slope.
4.80	Trail, bears E. and W.
9.50	A Fir, 3 ft. diam., on line, marked with 2 notches on N. and S. sides.
40.00	Set a basaltic stone, 24 x 10 x 8 ins., 18 ins. in the