

County Surveyor's Record, Douglas County, Oregon

8949

Willamette Meridian, 3rd. Offset, West Bdy. of T. 33 S., R. 5 W.
as surveyed by Butler Ives and Geo. W. Hyde, Deputy Surveyors,
under contract No. 39, dated January 4, 1854.

CHAINS	193rd. MILE
	South, on W. bdy. of sec. 6.
	Va. 18*20'E.
15.50	To a ravine, course NE.
15.50	Commence steep ascent.
39.50	Summit of a high ridge, course N.60*E and S.60*W.
39.50	Commence steep descent.
40.00	Set $\frac{1}{4}$ sec. post from which
	A B. Oak, 14 ins. diam., bears S.32*W., 48 lks. dist.
	A B. Oak, 12 ins. diam., bears S.60*E., 13 lks. dist.
	Va. 18*15'E.
40.00	Enter Oak and Pine openings.
74.73	A B. Oak, 18 ins. diam.
76.00	Leave Oak openings and enter Fir timber.
80.00	Set post cor. of secs. 6, 7, 1 and 12, from which
	A B. Oak, 14 ins.diam., bears S.47*W., 78 lks. dist.
	A B. Oak, 14 ins. diam., bears N.53*W., 108 lks. dist.
	A B. Oak, 24 ins. diam., bears S.53*E., 44 lks. dist.
	A Redwood, 14 ins. diam., bears N.51*E., 33 lks. dist.
	Land, hilly.
	Soil, 2nd. rate, reddish clay loam.
	Timber, Fir, B. Oak, Laurel, Y. Pine, Redwood and openings on S. half.
	194th MILE
	South, on W. bdy. of sec. 7.
	Va. 18*10'.
12.50	Foot of descent.
12.50	Stream 6 lks. wide, course S.60*W.
12.50	Commence steep descent on NW. slope of hill.
19.21	Fir, 18 ins. diam.
28.50	Summit of ridge, course NW and SE.
28.50	Commence descent on SE. slope.
40.00	Set a $\frac{1}{4}$ sec. post from which
	A B. Oak, 6 ins. diam., bears N.13*W., 15 lks. dist.