

## County Surveyor's Record, Douglas County, Oregon

4

## Subdivisions of T. 33 S., R. 5 W.

CHAINS		
	North, 1'W between secs. 13 and 14.	
	Va. 19°E.	
	Ascend mountain on S slope through dense underbrush.	
8.00	Summit of Main Divide runs NE and SW.	+100
	Descend on steep NW slope of mountain.	
15.00	Enter timber.	
19.80	A Fir, 40 ins. diam. line tree marked with 2 notches on N and S sides.	
40.00	Set basaltic stone 10 x 10 x 10 ins., 7 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W face from which A Fir, 18 ins. diam., bears N.19°E., 200 lks. dist. marked $\frac{1}{4}$ S B T. A Fir, 8 ins. diam., bears S.50°W., 416 lks. dist. marked $\frac{1}{4}$ S B T.	
45.00	A Fir, 24 ins. diam. line tree marked with 2 notches on N and S sides.	
45.50	Head of ravine bears NW. and foot of main descent.	-400
	Along about level on W slope of mountain.	
54.50	Edge of wide spring, 100 lks. wide, course W, and gradually ascend on W slope.	
60.70	A Fir, 14 ins. diam. line tree marked with 2 notches on N and S sides.	
70.00	Top of ascent +50 ft. and divide bears NW and S.30°E. Descend on NE slope of mountain.	
80.00	Set basaltic stone, 20 x 8 x 6 ins. 20 ins. in the ground at the foot of a sloping bluff, 40 ft. high for cor. to secs. 11, 12, 13 and 14, marked with 4 notches on the S and 1 notch on the E edges from which A Cedar, 24 ins. diam., bears N.51°E., 60 lks. dist. marked T 33 S R 5 W S 12 B T. A Fir, 18 ins. diam., bears S.21°20'E., 78 lks. dist. marked T 33 S R 5 W S 13 B T.	-100