

County Surveyor's Record, Douglas County, Oregon

13

Subdivisions of T. 33 S., R. 5 W.

CHAINS		
	North 2°W between secs 22 and 23. Va 18°45'E.	
	Descend mountain on NW slope.	
14.60	Foot of descent and ravine bears W	-300
	Along gradually ascending on W slope.	
24.75	A Fir, 30 ins diam. line tree, marked with 2 notches on N and S sides.	
28.35	A Matherone cut off 6 ft. high, squared 4 inches for cor. to some mining claim.	
32.30	Spring branch 4 lks. wide, course S.80°W, and ascend more rapidly.	
40.00	Set basaltic stone 16 x 12 x 8 ins. 11 ins. in the ground for $\frac{1}{4}$ sec. cor marked $\frac{1}{4}$ on W face from which A Y. Pine, 6 ins. diam., bears N.38 $\frac{1}{2}$ °E, 58 lks. dist. marked $\frac{1}{4}$ S B T. A Fir, 10 ins. diam., bears S.25°E., 85 lks. dist. marked $\frac{1}{4}$ S B T.	
	Ascend through scattering timber.	
51.30	Top of mt. spur, bears SW and a Y. Pine, 18 ins. diam. line tree marked with 2 notches on N and S sides.	
69.00	Summit of main divide bears E and W	+400
	Descend on N slope and begin to enter dense timber 100 ft	
80.00	Set basaltic stone 20 x 10 x 6 ins. 15 ins. in the ground for cor. to secs. 14, 15, 22 and 23, marked with 3 notches on the S and 2 notches on the E edges from which A Y. Pine, 24 ins. diam., bears N.44°E., 29 lks. dist. marked T 33 S R 5 W S 14 B T. A Cedar, 24 ins. diam., bears S.54°E., 61 lks. dist. marked T 33 S R 5 W S 23 B T. A Fir, 18 ins. diam., bears S.45°30'W., 51 lks. dist. marked T 33 S R 5 W S 22 B T. A Cedar, 16 ins. diam., bears N.56°W., 50 lks. dist. marked T 33 S R 5 W S 15 B T.	