

## County Surveyor's Record, Douglas County, Oregon

16

## Subdivisions of T. 33 S., R. 5 W.

CHAINS

A Fir, 16 ins. diam., bears N.29\*E., 14 lks. dist.  
marked T 33 S R 5 W S 11 B T.

A live Oak, 8 ins. diam., bears S.50\*E., 21 lks.  
dst. marked T 33 S R 5 W S 14 B T.

A Cedar, 36 ins. diam., bears S.68\*W., 16 lks. dist.  
marked T 33 S R 5 W S 15 B T.

A Matherone, 8 ins. diam., bears N.20\*W., 28 lks.  
dist. marked T 33 S R 5 W S 10 B T.

Land, mountainous, broken, rough, sloping to the NW.  
Heavy timber of Fir, Cedar, Pine and Matherone.  
Dense underbrush of Laurel, Hazel, small Fir, and  
Matherone.

Soil 2nd rate, gravelly.

June 6, 1894.

South 89\*17'E on a random line between secs. 11 and 14.  
Va 21'E.

40.00 Set temp.  $\frac{1}{2}$  sec. cor.

80.48 Intersect N and S line 16 lks. N of cor. to secs., 11  
12, 13 and 14.

Thence I run N.89\*10'W on a true line bet. secs. 11 and 14.  
Va 21\*40'E.

Ascend 100 ft. on E slope of bluffs to summit at

2.00 Descend on W slope of bluffs to

6.00 and then continue descending on N slope.

12.50 A Fir, 40 ins. diam., line tree, marked with 2 notches  
on E and W sides.

23.40 continue descending on SW slope to

35.40 A creek, 10 lks. wide, course N.70\*W and descend on  
NW slope.

40.24 Set a basaltic stone 10 x 10 x 6 ins. 7 ins. in the  
ground for  $\frac{1}{2}$  sec. cor. marked  $\frac{1}{2}$  on N side from which