

County Surveyor's Record, Douglas County, Oregon

17

Subdivisions of T. 33 S., R. 5 W.

CHAINS

A Fir, 22 ins. diam., bears N.55*W., 10 lks. dist.
marked $\frac{1}{4}$ S B T.

A Fir, 16 ins. diam., bears S.55*E., 7 lks. dist.
marked $\frac{1}{4}$ S B T.

50.10 A Fir, 24 ins. diam., line tree marked with 2 notches
on E and W sides continue descending on NW slope to

80.48 The cor. to secs. 10, 11, 14 and 15 about 1200 ft.
below top of bluff at 2.00 chs.

Land, mountainous, broken, rough sloping to the N and NW.

Heavy timber of Fir, Cedar, Pine and Matherone.

Dense underbrush of Hazel, Laurel, Matherone, small
Fir, Cedar and Vine Maple.

Soil E $\frac{1}{2}$ 4th rate, rocky W $\frac{1}{2}$ 3rd rate, gravelly.

June 6, 1894.

North 2'W between secs. 11 and 10.

Va 21*E.

Descend 100 ft. along W slope to

5.00 foot of descent and creek 5 lks. wide, course W.

5.30 A Fir, 36 ins. diam. line tree marked with 2 notches
On N and S sides, and ascend steep S slope of slate
rock.

10.00 Top of steep ascent +250 and descend along steep W slope.

20.00 Mt. spur bears N.20*W, and descend on NE slope.

30.65 Miners ditch bears W.

33.05 Foot of descent -500 ft. and creek 10 lks. wide, course W.
Ascend on S slope of mountain.

35.00 Road (wagon) bears E and W.

40.00 A Fir, 10 ins. diam. which I marked $\frac{1}{4}$ S on W side for
 $\frac{1}{4}$ sec. cor. from which

A Fir, 24 ins. diam., bears N.53*E., 19 lks. dist.
marked $\frac{1}{4}$ S B T.

A Fir, 14 ins. diam., bears S.44*W., 20 lks. dist.
marked $\frac{1}{4}$ S B T.