

## County Surveyor's Record, Douglas County, Oregon

22

## Subdivisions of T. 33 S., R. 5 W.

CHAINS

Therefore, I return to temp. cor. to secs. 34 and 35 T 32 S R 5 W and moved the same E 20 lks. (being half way between the  $\frac{1}{2}$  sec. cors. E and W of the same) and reestablish the cor. to secs. 34 and 35 T 32 S R 5 W at that point by setting a basaltic stone 12 x 10 x 8 ins. 8 ins. in the ground marked with 2 notches on the E and 4 notches on the W edges from which

A Fir, 10 ins. diam., bears N.23\*30'E., 26 lks. dist. marked T 32 S R 5 W S 35 B T.

A Fir, 10 ins. diam., bears S.41\*E., 52 lks. dist. marked T 33 S R 5 W S 2 B T.

S Pine, 6 ins. diam., bears N.51\*W., 35 lks. dist. marked T 32 S R 5 W S 34 B T.

From the cor. established to secs. 34 and 35 T 32 S R 5 W.

Thence I run W on N bdy. of Tp. 4.90 chs.

Va 18\*E.

to the intersections of N and S line between secs. 2 and 3 for closing corner. The S bdy. of secs. 34 and 35 T 32 S R 5 W between  $\frac{1}{2}$  sec. cors. being 40 lks. less than 80.00 chs. makes my closing within limits on 50 lks. Therefore at point of intersection for closing cor. on N bdy. of Tp. 4.90 chs. W of cor. established for Tp. cor. to secs. 34 and 35 T 32 S R 5 W, I set a basaltic stone 16 x 8 x 6 ins. 11 ins. in the ground for closing cor. to secs. 2 and 3 marked C C with 2 notches on the E and 4 notches on W edges from which

A Fir, 12 ins. diam., bears S.62\*E., 34 lks. dist. marked T 33 S R 5 W S 2 B T.

A Matherone, 8 ins. diam., bears S.86\*W., 8 lks. dist, marked T 33 S R 5 W S 3 B T.