

County Surveyor's Record, Douglas County, Oregon

30

Subdivisions of T. 33 S., R. 5 W..

CHAINS  
55.45

A Fir, 48 ins. diam line tree, marked with 2 notches on N and S sides, and ft. of high mountain.

Ascend mountain on S slope.

67.50

Mt. spur bears SE and ascend on SE slope.

76.50

Top of ascent and mt. spur, bears S. E.

+400

Descend 50 ft. along SE slope to

80.00

Set a basaltic stone 12 x 8 x 8 ins. 8 ins. in the ground for cor. to secs. 3, 4, 9 and 10, marked with 5 notches on the S and 3 notches on the E edges from which

A Fir, 36 ins. diam., bears N.68\*E., 44 lks. dist. marked T 33 S R 5 W S 3 B T.

A Fir, 12 ins. diam., bears S.45\*E., 4 lks. dist. marked T 33 S R 5 W S 10 B T.

A Matherone, 10 ins. diam., bears S.75\*W., 15 lks. dist, marked T 33 S R 5 W S 9 B T.

A Fir, 10 ins. diam., bears N.34\*W., 14 lks. dist. marked T 33 S R 5 W S 4 B T.

Land, mountainous, broken, rough.

Heavily timbered with Fir, Matherone, Cedar and Pine.

Dense underbrush of Hazel, small Fir, Matherone and live Oak, more especially on the S 40.00 chs.

Soil S 40.00 3rd. rate, and N. 40.00 chs. 2nd rate. all slate, gravel.

June 14, 1894.

East, on a random line between secs. 3 and 10.

Va 19\*E.

40.00

Set temp. 1/4 sec. cor.

80.23

Intersect N and S line 21 lks. N of cor. to secs. 2 and 3, 10 and 11.

Thence I run N.89\*51'W on a true line between secs. 3 and 10.

Va 19\*E.

Ascend mountain on NE slope.