

35

Subdivisions of T. 33 S., R. 5 W.

CHAINS

A Fir, 4 ins. diam., bears S.56*W., 9 lks. dist.

T 33 S R 5 W S 17 B T.

A Fir, 6 ins. diam., bears N.24*30'W., 18 lks. dist.

T 33 S R 5 W S 8 B T.

Land, mountainous, broken, rough.

Heavy timber of Fir, Pine, Cedar, and Oak.

Dense underbrush of small Fir, Hazel, and live Oak.

Soil, 3rd rate, gravelly.

June 19, 1894.

East on a random line between secs. 9 and 16.

Va 19*E.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.66 Intersect cor. to secs. 9, 10, 15 and 16.

Thence I run West on a true line bet. secs. 9 and 16.

Va 19*E.

Descend 30 ft. on W slope to

1.25 Foot of descent and ravine. Ascend on NE slope.

13.35 A Fir, 24 ins. diam. line tree, marked with two notches on E and W sides.

13.90 Top of ridge, bears NW and SE 250 ft. above ravine at 1.25 chs. Descend mountain on SW slope.

37.96 A Fir, 30 ins. diam. line tree, marked with two notches on E and W sides.

40.33 Set a post 3 ft. long, 4 ins. sq. 24 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N side from which

A Fir, 12 ins. diam., bears N.60*30'E., 69 lks. dist, marked $\frac{1}{4}$ S B T.

A Fir, 8 ins. diam., bears S.75*W., 46 lks. dist. marked $\frac{1}{4}$ S B T.

44.55 Ravine 15 ft. deep bears S.70*W.

55.51 Mining ditch bears SE.

56.16 A Fir, 24 ins. diam. line tree marked with two notches on E and W sides.