

## County Surveyor's Record, Douglas County, Oregon

42

## Subdivisions of T. 33 S., R. 5 W..

CHAINS

A W. Oak, 4 ins. diam, bears N.57\*E., 4 lks. dist.

marked T 33 S R 5 W S 8 B T.

A W. Oak, 5 ins. diam., bears S.66\*E., 3 lks. dist.

marked T 33 S R 5 W S 17 B T.

A W. Oak, 4 ins. diam., bears S.16\*W., 8 lks. dist.

marked T 33 S R 5 W S 18 B T.

A W. Oak, 4 ins. diam., bears N.16\*30'W., 46 lks.

dist, marked T 33 S R 5 W S 7 B T.

Land, mountainous, broken, high and rough.

Heavy timber of Fir, Pine, Oak, and Matherone, and Cedar.

Dense underbrush of small Fir, Hazel, Oak and Matherone.

Soil 3rd rate, gravelly.

June 27, 1894.

South 89\*45'E on a random line bet. secs. 8 and 17.

Va 18\*50'.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.80.17 Intersect N and S lines at the cor. to secs. 8, 9,  
16 and 17.Thence I run N.89\*45'W on a true line bet. secs. 8.  
and 17.

Va 19\*E.

Ascend along N slope.

7.37 A Fir, 36 ins. diam., line tree marked with two notches  
on E and W sides.

10.35 Top of ascent -100 and descend on steep W slope 200 ft. to

15.90 Foot of descent and branch 2 lks. wide, course N.

Ascend steep E slope 200 ft. to

22.17 Mt. point bears N and ascend to

34.80 Top of ascent and mt. spur bears N.15\*W.

Descend mt. on W slope.

40.09 Set a post 3 ft. long, 3 ins. sq, 24 ins. in the ground  
for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$ S on N side from which