

## County Surveyor's Record, Douglas County, Oregon

4/3

## Subdivisions of T. 33 S., R. 5 W.

CHAINS

Soil 3rd rate, gravelly.

June 28, 1894.

North 4'W bet. secs. 7 and 8.

Va 18°E.

Ascend on W slope of mountain 75 ft. to

- 12.00 Top of ascent on W slope, and descend on W slope.
- 17.88 A Fir, 24 ins. diam., line tree marked with 2 notches on N and S sides.
- 22.50 Mt. spur, bears NW and descend rapidly on steep N rocky slope.
- 40.00 Set basaltic stone 12 x 10 x 8 ins. 8 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  on W side from which  
 A Fir, 18 ins. diam., bears N.11°30'W., 38 lks. dist, marked  $\frac{1}{4}$  S B T.  
 A Fir, 24 ins. diam., bears S.15°E., 61 lks. dist. marked  $\frac{1}{4}$  S B T.
- 48.00 Foot of steep N to NE descent, about 1000 ft. below point at 12.00 chs.
- 50.70 Wolf Creek, 20 lks. wide, course NW.
- 51.60 Wagon road E and W leading to Wolf Creek Station.
- 52.50 Foot of mountain and begin to ascend.
- 55.75 Cut 10 ft. deep bears SW.
- 65.00 Begin to ascend on steep SW slope.
- 74.80 Ravine and spring branch 3 lks. wide, course SW, and ascend on SE slope.
- 80.00 Set basaltic stone 18 x 8 x 8 ins. 12 ins. in the ground for cor. to secs. 5, 6, 7 and 8 marked with 5 notches on the S and E edges +500 from which  
 A W. Oak, 5 ins. diam., bears N.65°30'E., 19 lks. dist, marked T 33 S R 5 W S 5. B T.  
 A W. Oak, 10 ins. diam., bears S.83°30'E., 19 lks. dist, marked T 33 S R 5 W S 8 B T.  
 A B. Oak, 5 ins. diam., bears S.34°30'W., 30 lks. dist, marked T 33 S R 5 W S 7 B T.