

County Surveyor's Record, Douglas County, Oregon

44

Subdivisions of T. 33.S., R. 5 W.

CHAINS

A B. Oak, 8 ins. diam., bears N.42*W., 15 lks. dist.
marked T 33 S ^N 5 W S 6 B T.

Land, mountainous, broken, rough.

Heavy timber, of Fir, Oak, Matherone, Pine and Cedar
Dense underbrush of Hazel, small Fir, Vine Maple and Oak
Soil, S 40.00 chs, 3rd rate. and N 40.00 chs, 2nd rate.

June 28, 1894.

S.89*45'E on a random line bet. secs 5 and 8.

Va 18*50'E.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.06 Intersect N and S line 49 lks. N of cor. to secs. 4, 5,
8 and 9.

Thence I run N.89*24'W on a true line bet. secs. 5 and 8.

Va 19'E.

Descend on S slope.

1.38 Ravine and spring branch 2 lks. wide, course SW.

3.48 Ravine, 10 ft. deep bears SW.

6.95 Ravine, 15 ft. deep bears SW.

7.63 A Cedar, 30 ins. diam. line tree, marked with 2 notches
on E and W sides.

12.80 Foot of descent -150 and ascend along S slope.

19.52 A B. Oak, 36 ins. diam line tree, marked with 2 notches
on E and W sides.

27.20 A B. double Oak, 40 ins. diam line tree, marked with
2 notches on E and W sides.

32.80 Top of steep SE ascent and mt. spur, bears S.

Ascend more gradually on S slope.

38.75 Ravine, 10 ft. deep bears S.

40.03 A B. Oak, 6 ins. diam. which I marked $\frac{1}{2}$ S on N side for
 $\frac{1}{4}$ sec. cor. from which

A B. Oak, 16 ins. diam., bears N.29*E., 37 lks. dist.
marked $\frac{1}{4}$ S B T.

A B. Oak, 7 ins. diam., bears S.44*W., 18 lks. dist.
marked $\frac{1}{4}$ S B T.