

## County Surveyor's Record, Douglas County, Oregon

48

## Subdivisions of T. 33 S., R. 5 W.

CHAINS

61.04 A Fir, 48 ins. diam., line tree, marked with two notches on N and S sides.

69.00 Creek, 8 lks. wide, course N.30°E., and continue descending on W slope.

81.20 Intersect North bdy. of Tp. set temp. closing cor. about 900 ft. below divide at 28.05 chs.

Thence I run

E along N bdy. of Tp. W slope.

Va 19°E.

5.70 Intersect cor. to secs. 31 and 32 T 32 S R 5 W

determined by bearing trees as post was missing at point for cor. set a quartz stone 10 x 8 x 8 ins. 7 ins. in the ground for cor. to secs. 31 and 32 T 32 S R 5 W marked with 5 notches on the E and 1 notch on the W edges from which

A Fir, 14 ins. diam., bears N.32°E., 37 lks. dist. with well defined blazes.

A Laurel, 10 ins. diam., bears S.40°W., 45 lks. dist. with well defined blazes.

The SE and NW trees being burnt down with marks partly grown over, I reestablish

A Fir, 30 ins. diam., bears N.42°W., 64 lks. dist. marked T 32 S R 5 W S 31 B T.

A Fir, 24 ins. diam., bears S.41°E., 100 lks. dist. marked T 33 S R 5 W S 5 B T.

Va 18°10'E.

I now return to the temp. closing cor. to secs. 5 and 6 which is 5.70 chs. W of cor. to secs. 31 and 32 T 32 S R 5 W and set a basaltic stone 18 x 10 x 5 ins. 12 ins. in the ground for closing cor. to secs 5 and 6 marked C C with 5 notches on the E and 1 notch on the W edges from which