

County Surveyor's Record, Douglas County, Oregon

9001

Exterior Lines of Tp. 33, S., R. 6 W.,
as surveyed by Wells Lake, Deputy Surveyor,
under Contract No. 54, dated Feb. 19, 1855.

CHAINS		
	South on West boundary of Sec. 6	
		Var. 19°30'E.
6.00	Leave creek bottom course NE and W (Foot of mountain)	+ 10
8.22	A Fir, 24 ins. diam.	+ 75
18.00	Summit of line on spur course NW	+ 150
22.10	Branch 2 lks. wide, course NW	- 125
35.25	Ravine on Mountain Side, course NW	+ 200
40.00	Set quarter sec. post on steep N descent, from which; A Chinquapin, 10 ins. diam., bears N. 14°W., 60 lks. A Cedar, 12 ins. diam., bears S. 40°E., 22 lks.	+ 150
		Var. 19°15'E.
62.50	Summit of mountain course E and W	+ 600
80.00	Set post cor. to secs. 1, 6, 7 and 12 on S slope from which; A Laurel, 4 ins. diam., bears N. 25°E., 45 lks. A Laurel, 4 ins. diam., bears N. 47°W., 29 lks. A Laurel, 3 ins. diam., bears S. 79°W., 30 lks. A Laurel, 4 ins. diam., bears S. 49°E., 55 lks.	- 200
	This mile runs over high mountains of rock and decayed granite with some slate and quartz. Fir and Laurel timber with thick Manzaneta and ground unfit for settlement.	
	South on the West boundary of Sec. 7	
		Var. 18°50'E.
6.17	A Fir, 30 ins. diam.,	- 100
15.60	Branch 6 lks. wide course S. 80°W	- 100
17.50	Summit of line on spur course West	+ 50
22.40	Branch 6 lks. wide course NW	- 75
40.00	Set quarter Sec. Post (on steep NW descent) from which; A Fir, 24 ins. diam., bears N. 32°W., 41 lks. A Fir, 36 ins. diam., bears N. 35°E., 19 lks.	
		Var. 19°10'E.