

County Surveyor's Record, Douglas County, Oregon

Subdivisions of Tp. 33 S., R 6 W., as surveyed by W. H. Byars, Deputy Surveyor, under Contract No.431, dated March 29, 1882.

CHAINS	
	North between Secs. 20 and 21 * * * * *
	Va.18*E
80.00	Set an Oak post, 4 feet long 4 ins. sqr. 22 ins. in the ground, marked T 33 S R 6 W S 16 on NE face S 21 on SE face S 20 on the SW face and S 17 on the NW face also 3 notches on the South and 4 notches on the East Angles of the same, from which;
	A B Oak, 7 ins. diam., bears N.34*E., 17 lks. dist, marked T 33 S R 6 W S 16 B T.
	A B Oak, 10 ins. diam., bears S.34*E., 16 lks. dist. marked T 33 S R 6 W S 21 B T.
	A Laurel 10 ins. diam., bears S.48*W., 77 lks. dist. marked T 33 S R 6 W S 20 B T
	A Fir, 14 ins. diam., bears N.32*W., 30 lks. dist. marked T 33 S R 6 W S 17 B T.
	Land mountainous 2nd rate.
	Timber chiefly Fir, Cedar, Pine, Oak, and Laurel.
<hr/>	
	East on Random Line between Secs. 16 and 21
	Va.18*E.
16.80	Railroad Line, course S 80W
29.75	Water Ditch, course S 80 W
34.75	Water Ditch, course W
38.00	Creek 6 lks. wide course SE
39.10	Enter Field course NW and SE
40.00	Set temporary 1/4 Sec. Cor.
42.50	Leave Field course NE and SW
43.50	Wagon Road course N 80*E
46.50	Wagon Road course S 80*E
56.90	Creek 5 lks. wide course S 30*E
60.00	Water Ditch course N 80*W
80.20	Intersect 35 lks. North of corner, to secs. 15, 16, 21 and 22 Old corner destroyed reestablished same as per instructions, from which;
	A Y pine, 24 ins. diam., bears N.59*E., 257 lks.