

9030
 County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 33 S., R 7 W.

CHAINS

A Chinquapin, 10 ins. diam., bears N.46*E., 16 lks. dist., Marked T 33 S R 6 W S 7 B T.

A Chinquapin, 8 ins. diam., bears S.34*E., 14 lks. dist., Marked S 18 B T.

A Laurel, 12 ins. diam., bears S.38*W., 53 lks. dist. Marked T 33 S R 7 W S 13 B T.

A Chinquapin, 6 ins. diam., bears N.25*W., 17 lks. dist., no marks perceptible.

Thence, S.89*27*W., on true line between secs. 12 and 13, with same Va.

39.96 Set Fir post, 3 feet long, 3 ins. square, 18 ins. in the ground, for $\frac{1}{2}$ sec. corner, marked $\frac{1}{2}$ S on N. face, from which

A Fir, 30 ins. diam., bears S.2*E., 29 lks. dist. Marked $\frac{1}{2}$ S B T.

A Fir, 42 ins. diam., bears N.18*E., 70 lks. dist. Marked $\frac{1}{2}$ S B T.

79.92 The corner to secs. 11, 12, 13 and 14.

Land, rolling and hilly.

Soil, third rate.

Timber, chiefly, Fir and Pine with some Laurel and Chinquapin.

February 9, 1882.

North between secs. 11 and 12.

Va. 17*30*E.

Steep descent.

7.00 A creek, 3 lks. wide, Course N.20*E.

27.08 A creek, 15 lks. wide, Course N.20*W.

Ascend along steep sidehill facing W.

40.00 A Fir tree, 16 ins. in diam., which I marked $\frac{1}{2}$ S on a W. face for the $\frac{1}{2}$ sec. corner, from which