

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 33 S., R. 7 W.

CHAINS

A S. Pine, 26 ins. diam., bears N.75\*W., 30 lks. dist., marked  $\frac{1}{4}$  S B T.

A S. Pine, 24 ins. diam., bears S.85\*E., 15 lks. dist., marked  $\frac{1}{4}$  S B T.

77.00 Top of spur, Course NW.

Very steep descent to

80.00 Set Laurel post, 4 feet long, 4 ins. square, 2 feet in the ground for corner to secs. 1, 2, 11 and 12, marked T 33 S R 7 W S 1 on NE., S 12 on SE., S 11 on SW. and S 2 on NW. faces, with 5 notches on S and 1 notch on E. edges, from which

A Fir, 14 ins. diam., bears N.35\*E., 78 lks. dist., Marked T 33 S R 7 W S 1 B T.

A Fir, 26 ins. diam., bears S.86\*E., 24 lks. dist., Marked T 33 S R 7 W S 12 B T.

A Fir, 14 ins. diam., bears S.78\*W., 38 lks. dist., Marked T 33 S R 7 W S 11 B T.

A Fir, 14 ins. diam., bears N.76\*W., 34 lks. dist., Marked T 33 S R 7 W S 2 B T.

Land, mountainous.

Soil, third rate.

Timber, chiefly, Fir and Pine, with some Laurel and Chinquapin.

East on Random line between secs. 1 and 12.

Va. 17\*30'E.

Along steep mountain side facing N.

27.00 A creek, from E., 8 lks. wide, Course N.60\*W.

29.80 Leave same, from SE.

37.40 A creek, 3 lks. wide, Course S.60\*W.

40.00 Set temporary  $\frac{1}{4}$  sec. corner, steep ascent.

79.65 Intersect E. boundary of Township 80 lks. South of