

Subdivisions of T. 33 S., R. 7 W.

CHAINS

ground marked $\frac{1}{4}$ S on W. side for the $\frac{1}{4}$ sec. corner.

Made stone mound about same. No witness trees near and pits impracticable.

46.00 Top of spur, Course W. Begin descent.

81.52 Intersect North boundary of Township 10.41 chs. East of established corner to secs. 35 and 36 T. 32 S R 7 W. Set a Fir post, 4 feet long, 4 ins. square, 24 ins. in the ground for closing corner to secs. 1 and 2, marked C C T 33 S R 7 W on S., S 1 on E., S 2 on W., faces; also 1 notch on E. and 5 notches on W. faces, from which

A Cedar, 36 ins. diam., bears S.35*E., 20 lks. dist.

Marked T 33 S R 7 W S 1 B T.

A Fir, 32 ins. diam., bears S.44*W., 28 lks. dist.

Marked T 33 S R 7 W S 2 B T, also

A Fir, 56 ins. diam., bears N.65*W., 21 lks. dist.

Marked T 32 S R 7 W S 36 B T.

Land, mountainous and broken.

Soil, rocky, third rate.

Timber, chiefly, Fir, Pine, and Cedar.

February 13, 1882.

North between secs. 22 and 23.

Va. 17*30*E.

9.50 Top of spur, Course W., steep descent.

26.50 A creek, 12 lks. wide, Course W., steep ascent.

37.00 Top of spur, Course SW., along steep mountain side.

40.00 Set a Laurel post, 3 feet long, 3 ins. square, 20 ins. in the ground, marked $\frac{1}{4}$ S on W. side, for the $\frac{1}{4}$ sec. corner, from which

A Live Oak, 12 ins. diam., bears S.70*E., 34 lks.

dist., marked $\frac{1}{4}$ S B T, also

A Laurel, 6 ins. diam., bears N.65*W., 19 lks. dist.,

Marked $\frac{1}{4}$ S B T.