

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 33 S., R. 7 W.

CHAINS	East, on random line bet. secs. 10 and 15. Va. 17*30'E.
29.50	Top of ridge, course NW. and S.80*E.
40.00	Set temp. $\frac{1}{4}$ Sec. cor.
50.00	Top of ridge, course NE and S.60*W.
72.00	Steep descent.
80.09	Intersect N. and S. line 56 lks. South of cor. to secs. 10, 11, 14 and 15; thence S.89*36'W., on true line bet. secs. 10 and 15.
40.05	Marked a Chinquapin, 10 ins. diam., $\frac{1}{4}$ S on W side, for $\frac{1}{4}$ sec. cor. from which A Chinquapin, 5 ins. diam., bears S.72*E., 42 lks. dist., marked $\frac{1}{4}$ S B T. A Fir, 40 ins. diam., bears N.33*W., 20 lks. dist., marked $\frac{1}{4}$ S B T.
80.09	To cor. to secs. 9, 10, 15 and 16. Land, rough, mountainous and broken; soil, third rate. Timber, fir, oak, laurel and cedar.
	North, bet. secs. 9 and 10. Va. 17*30'E.
26.00	Top of high ridge, course E and W.; steep descent.
40.00	Set a laurel post, 3 ft. long, 3 ins. in diam., 2 ins. in the ground, marked $\frac{1}{4}$ S on W side for the $\frac{1}{4}$ sec. cor. from which A Fir, 22 ins. diam., bears N.35*E., 20 lks. dist. marked $\frac{1}{4}$ S B T. A Laurel, 12 ins. diam., bears N.30*W., 130 lks. dist., marked $\frac{1}{4}$ S B T.
47.60	A creek, 12 lks. wide, course NE.
74.70	A creek, 9 lks. wide, course E; steep ascent.
80.00	Set a laurel post, 4 ft. long, 4 ins. square, 2 ft. in the ground, marked T 33 S R 7 W S 3 on NE., S 10 on SE., S 9 on SW., and S 4 on NW. faces, also 5 notches on the S and 3 on the E angles of same for the cor.