

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 33 S., R. 7 W.

CHAINS	<p>North, on true line bet. secs. 3 and 4.</p> <p style="text-align: right;">Va. 17*30'E.</p> <p>40.00 Set laurel post, 3 ft. long, 3 ins. sq., 18 ins. in the ground, mkd. <math>\frac{1}{4}</math> S. on W. side, for the <math>\frac{1}{4}</math> sec. cor. from which,</p> <p style="padding-left: 40px;">A laurel, 8 ins. diam., bears N.15*E., 53 lks. dist. marked <math>\frac{1}{4}</math> S B T</p> <p style="padding-left: 40px;">A laurel, 8 ins. diam., bears N.52*W., 95 lks. dist. marked <math>\frac{1}{4}</math> S B T</p> <p>47.50 Top of spur, course NE; descend.</p> <p>65.00 Moderate descent.</p> <p>84.12 Intersect N. bdy. of Tp., 10 chs. E. of cor. to secs. 33, and 34, T. 32 S., R. 7 W.</p> <p>Set a chinquapin post, 4 ft. long, 4 ins. sq., mkd.</p> <p style="padding-left: 20px;">T 33 S R 7 W on S. side, S 3 and 3 notches on E. side, S 4 and 3 notches on W. and T 32 S R 7 W S 34 on N. faces of same for closing cor. bet. secs. 3 &amp; 4, from which</p> <p style="padding-left: 40px;">A fir, 38 ins. diam., bears S.20*E., 14 lks. dist. marked T 33 S R 7 W S 3 B T</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S.4*W., 16 lks. dist. marked T 33 S R 7 W S 4 B T</p> <p style="padding-left: 40px;">A fir, 40 ins. diam., bears N.34*W., 22 lks. dist. marked T 32 S R 7 W S 34 B T</p> <p>Land; mountainous, steep, 3rd rate.</p> <p>Timber; fir, pine, oak and laurel.</p>
	<p>West Bdy. of T. 33 S., R. 7 W., As surveyed by Oscar F. Thiel, U.S. Deputy Surveyor, under Contract No. 729, dated December 24, 1900.</p>
	<p>North, bet. secs. 13 and 18. *****</p> <p>80.00 Set a granite stone, 16x12x10 ins., 11 ins. in the ground for cor. to secs. 7, 12, 13 and 18, mkd. with 2 notches on N. and 4 notches on S. edges, from which</p> <p style="padding-left: 40px;">A Live Oak, 6 ins. diam., bears N.57*E., 14 lks. dist. marked T 33 S R 7 W S 7 B T.</p>