

## County Surveyor's Record, Douglas County, Oregon

## West Boundary of T. 33 S., R. 7 W.

## CHAINS

80.00

Set a sandstone, 14x12x10 ins., 10 ins. in the ground, for cor. of secs. 1, 6, 7 and 12, marked with 1 notch on N and 5 notches on S. edges, from which

A Fir, 40 ins. diam., bears N.38\*E., 48 lks. dist., marked T 33 S R 7 W S 6 B T.

A Fir, 30 ins. diam., bears S.54\*E., 37 lks. dist., marked T 33 S R 7 W S 7 B T.

A Chinquapin, 6 ins. diam., bears S.57\*W., 84 lks. dist., marked T 33 S R 8 W S 2 B T.

A Fir, 24 ins. diam., bears N.76\*W., 72 lks. dist., marked T 33 S R 8 W S 1 B T.

This cor. stands 20 ft. below top of ridge.

Land, mountainous and very rough; soil, rocky fourth rate.

Timber, fir, sugar pine, laurel, oak, chinquapin.

Undergrowth, a short prickly brush, 2 ft. high, name unknown.

Mountainous, or heavily timbered land, 80.00 chs.

North, bet. secs. 1 and 6.

Descend N. slope of mountain, covered heavily with timber.

12.00 A ravine, 60 ft. deep, course E., 75 ft. below sec. cor; begin ascent of S. slope.

24.35 A wagon road from Glendale to the gold mine, bears E and W; continue ascent.

40.00 Set a granite stone, 15x12x10 ins., 10 ins. in the ground for  $\frac{1}{2}$  sec. cor., marked  $\frac{1}{2}$  on W face, from which

A Fir, 24 ins. diam., bears N.33 $\frac{1}{2}$ \*E., 23 lks. dist., marked  $\frac{1}{2}$  S 6 B T.

A Fir, 44 ins., diam., bears S.2 $\frac{1}{2}$ \*W., 49 lks. dist., marked  $\frac{1}{2}$  S 1 B T.

This cor. stands 400 ft. above sec. cor.; continue ascent.

44.00 Top of dividing mountain ridge bet. the waters of Cow Creek and Rogue River, 50 ft. above  $\frac{1}{2}$  sec. cor.