

Subdivisions of T. 33 S., R. 7 W.

CHAINS	
47.00	Begin descent of N. mountain slope, covered with timber and a dense undergrowth of small firs and oaks.
80.00	Foot of descent; 400 ft. below top of divide, begin a gradual ascent of E. slope.
83.07	Intersect the 7th Standard Parallel S., 6.32 chs. E. of Stand. Tp. cor. of Tps. 32 and 33 S., Rs. 7 and 8 W., which is a pine post, mkd. and witnessed as described by the Surveyor General. At the point of intersection I set a pine post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for closing cor. of secs. 1 and 6, Tp. 33 S., Rs. 7 and 8 W., mkd. C C T 33 S on S., R 7 W S 6 on E., and R 8 W S 1 on W faces, with 6 grooves on SE., and W. faces, from which, A fir, 6 ins. diam., bears S.19*W., 131 lks. dist. marked T 33 S R 7 W S 6 B T A fir, 24 ins. diam., bears S.58*W., 56 lks. dist. marked T 33 S R 8 W S 1 B T Land; mountainous, soil gravelly, 3rd rate. Timber; fir, sugar pine, cedar, laurel, chinquapin. Undergrowth; poison laurel, small firs and hazel. Mountainous or heavily timbered land; 83.07 chs. connection line, 6.32 chs.
Subdivisions of T. 33 S., R. 7 W., as surveyed by Oscar F. Thiel, U.S. Deputy Surveyor, Under Contract No. 729, dated December 24, 1900.	
80.00	Thence I run N.0*01*W., bet. secs. 16 and 17. * * * * * Set a granite stone, 16x10x7 ins., 11 ins. in the ground for cor. to secs. 8, 9, 16 and 17, mkd. with 4 notches on E. and S. edges, and raised a mound of stone, 2 ft. base, 1½ ft. high, W. of cor. Pits impracticable. Land; mountainous, very rough; Soil; rocky, 4th rate. Timber; fir, pine, live oak, chinquapin, laurel.