

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 33 S., R. 7 W.

CHAINS

- 24.10 A creek, 10 lks. wide, Course N.20*E., begin a steep ascent of a rough E. mountainslope.
- 33.40 Top of spur, bears E. and W., 75 feet above stream begin steep descent.
- 36.55 A stream, 2 lks. wide, Course E., 80 feet below top of spur, begin ascent, steep and rough.
- 39.00 Top of spur, bears E. and W., 80 feet above stream, begin descent.
- 40.00 Set a Fir post, 3 feet long, 3 ins. square, 24 ins. in the ground for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ S 5 on W. face and 4 on E. face, from which
- A Laurel, 6 ins. diam., bears N.16*E. 37 lks. dist.
Marked $\frac{1}{4}$ S 4 B T.
- A Laurel, 9 ins. diam., bears N.46*W., 22 lks. dist.
Marked $\frac{1}{4}$ S 5 B T.
- August 6, 1901.
- 65.30 A stream, 2 lks. wide, Course NE., follow the E. slope of mountain.
- 84.09 Intersect the 7th Standard parallel South 10.82-chs. E. of corner to secs. 32 and 33, which having disappeared, I re-establish it, by setting a granite stone, 15 x 8 x 6 ins., 10 ins. in the ground, for standard corner of secs. 32 and 33, marked S C on N., with 4 grooves on E. and 2 notches on W. faces, and witnessed as described by the surveyor general.
- At the point of intersection I set a Pine post, 3 feet long, 4 ins. square, 24 ins. in the ground, for closing corner of secs. 4 and 5, marked C C T 33 S R 7 W on S. S 4 on E., and S 5 on W. faces, with 4 grooves on E., and 2 grooves on W. faces, from which
- A Chinquapin, 8 ins. diam., bears S.83*E., 134 lks. dist., marked T 33 S R 7 W S 4 B T.