

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 33 S., R. 7 W.

CHAINS

Mountainous or heavily timbered land or covered with dense undergrowth. 80.00 chs.

August 10, 1901.

East on a random line between secs. 8 and 17.

40.00 Set temporary $\frac{1}{2}$ sec. corner.

80.48 Intersect N. and S. line N. 32 lks. of corner of secs. 8, 9, 16 and 17.

Thence I run

N.89*46'W. on a true line between secs. 8 and 17.

Ascend a very steep and brushy E. mountainslope, covered heavily with timber, bears N. and S.

3.20 Top of ridge, bears N. and S., 75 feet above sec. corner begin descent of a steep and brushy W. slope.

22.40 A stream, 2 lks. wide, Course N.60*W., 250 feet below top of ridge, along N. slope.

30.00 Change to NW. slope.

40.24 Set a Fir post, 3 feet long, 3 ins. square, 24 ins. in the ground for $\frac{1}{2}$ sec. corner, marked $\frac{1}{2}$ S 8 on N. and 17 on S. face, from which

A Fir, 6 ins. diam., bears N.11*W., 35 lks. dist.,
Marked $\frac{1}{2}$ S 8 B T.

A Sugar Pine, 50 ins. diam., bears S.23*W., 26 lks. dist., Marked $\frac{1}{2}$ S 17 B T.

This corner stands 450 feet below top of ridge, begin gradual descent of NW. slope.

60.35 A fork of Reuben's Creek, 10 lks. wide, Course S.60*W., 100 feet below $\frac{1}{2}$ sec. corner, begin ascent of SE. slope.

63.45 A stream, 2 lks. wide, Course S., continue ascent.

75.00 Top of mountain spur, bears N. and S., 100 feet above creek.