

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 33 S., R. 7 W.

CHAINS	
4.00	Top of mountain ridge, dividing the waters of Cow Creek and Rogue River, 25 feet above sec. corner.
9.50	Begin descent of a NE. slope, enter large timber, bears E. and W.
16.50	Va. 19°E. (same was 19°32' at sec. corner) begin steeper descent, no underbrush.
19.50	Wagon road from Glendale to the Mines, bears E. and W., continue very steep descent of N. slope.
27.60	Foot of steep descent, 300 feet below top of divide, along E. slope covered by dense undergrowth.
33.50	Top of ascent, 40 feet above foot of descent begin steep descent, leave large Fir timber.
40.00	Set a granite stone; 18 x 9 x 6, 12 ins. in the ground for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ on W. face, from which A Laurel, 10 ins. diam., bears S.43°E., 34 lks. dist. Marked $\frac{1}{4}$ S 5 B T. A Fir, 12 ins. diam., bears N.30°W., 7 lks. dist., Marked $\frac{1}{4}$ S 6 B.T.
	Continue descending through scattering timber but a dense undergrowth.
45.60	Foot of descent, 60 feet below $\frac{1}{4}$ sec. corner, along E. slope.
48.00	Enter a new burn, bears E. and W.
63.00	Top of spur, bears E. and W., 300 feet above $\frac{1}{4}$ sec. corner, leave burn, burnt Manzanitas are worse than green underbrush, along E. slope.
81.00	Begin descent of N. slope.
83.56	Intersect 7th Standard corner of secs. 31 and 32, which is a Fir post, marked and witnessed as described by the surveyor general. I built a mound of stone around the the post, and as only the stump of 2 other bearing