

Resurvey of West Boundary of T. 33 S., R. 7 W.

CHAINS

A Pine, 8 ins. diam., bears N. 20\*W., 60 lks. dist.,  
mkd.  $\frac{1}{4}$  S 12 B T.

40.05 The  $\frac{1}{4}$  cor established for secs. 7 and 12, which is granite stone, 10x5x5 ins. above ground, firmly set, mkd. and witnessed as described by the surveyor general.

Hereafter this cor. will refer to sec. 7 only.

Reset stone with  $\frac{1}{4}$  facing E.

Obliterate markings on bearing tree referring to sec. 12 and take new bearing tree as follows:

A Pine, 8 ins. diam., bears N. 45\*E., 25 lks. dist.,  
mkd.  $\frac{1}{4}$  S 7 B T.

Thence N. 0\*57'E.

Asc. 525 ft over SW. slope to spur.

37.94 Set a diorite stone, 18 x 10 x 10 ins., 14 ins. in the ground, for cor. of secs. 1 and 12, mkd. with 1 notch on N. and 5 notches on S. edge; from which

A Pine, 12 ins. diam., bears S. 15\*W., 78 lks. dist.,  
mkd. T 33 S R 8 W S 12 B T.

A Pine, 8 ins. diam., bears N. 52\*W., 112 lks. dist.,  
mkd. T 33 S R 8 W S 1 B T.

39.50 Spur, slopes SE., desc. 5 ft. over NE. slope.

40.00 The cor. established for sec. 1, 6, 7 and 12, which is a sandstone, 12 x 10 x 5 ins., above ground, firmly set, mkd. and witnessed as described by the surveyor general.

Hereafter this cor. will refer to secs. 6 and 7 only.

Obliterate markings on bearing trees referring to secs. W of line.

Land, mountainous.

Soil, loose, coarse, rocky loam; third rate.

Timber, Fir, Pine, Madrona, Live Oak, Cedar and Maple.

Undergrowth, Chinquapin, Lilac, Live Oak and Buckhorn.