

County Surveyor's Record, Douglas County, Oregon

Resurvey of the West Boundary of T. 33 S., R. 7 W.

CHAINS	
	N. 0° 51' E., on W. bdy. of sec. 6. Desc. 160 ft. over NE slope, through heavy green timber and dense undergrowth.
11.70	Head of ravine, course SE., asc. 490 ft. over SE. slope to the old $\frac{1}{4}$ sec. cor.
24.45	Road, bears E. and W.
37.94	Set a granite stone 15 x 10 x 8 ins., 10 ins. in the ground for $\frac{1}{4}$ cor. of sec. 1, mkd. $\frac{1}{4}$ on W. face; from which A Madrona, 20 ins. diam., bears S. 20°W., 40 lks. dist., mkd. $\frac{1}{4}$ S 1 B T. A Fir, 10 ins. diam., bears N. 18°W., 45 lks. dist., mkd. $\frac{1}{4}$ S 1 B T.
40.03	The $\frac{1}{4}$ cor. established for secs. 1 and 6, which is a granite stone, 12 x 10 x 5 ins., above ground, firmly set, mkd., and witnessed as described by the surveyor general. Hereafter this cor. will refer to sec. 6 only. Reset stone with $\frac{1}{4}$ facing E. Obliterate markings on bearing tree referring to sec. 1 and take new bearing tree as follows: A Fir, 20 ins. diam., bears N. 25°E., 33 lks. dist., mkd. $\frac{1}{4}$ S 6 B T. Thence N. 0° 53' E. Asc. 5 ft. over SE. slope.
4.00	Ridge, bears NE. and SW.; desc. 750 ft. over N. slope.
39.60	Head of ravine, course E. Leave heavy green timber, bears E. and W. continue through heavy standing dead timber. Asc. 40 ft. over SE. slope
42.93	The closing cor. of Tps 33 S., Rs 7 and 8 W., which is a pine post, 4 x 4 ins., 12 ins. above ground, firmly set, mkd. and witnessed as described by the surveyor general.