

County Surveyor's Record, Douglas County, Oregon

Portion of East boundary of T. 33 S., R. 9 W.

CHAINS

survey 80.00.

October 13, 1909.

At the cor. of secs. 7, 12, 13 and 18, thence I run
North between secs. 7 and 12.

Along East slope over mountainous land covered with
heavy timber and dense undergrowth exceptionally
difficult to survey.

23.00 Branch, 2 lks. wide, course S E,

Ascend.

40.00 Set a Fir post, 3 ft. long, 4 ins. sq., 24 ins. in the
ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S. 12 on W. face, and
7 on E. face, from which

A Pine, 36 ins. diam., bears N. $1\frac{1}{2}$ *E., 165 lks. dist.,
mkd. $\frac{1}{4}$ S 7 B T.

A Fir, 10 ins. diam., bears N. $48\frac{1}{2}$ *W., 148 lks. dist.,
mkd. $\frac{1}{4}$ S 12 B T.

41.96 "Dutch Henry's" trail on top of ridge, bears E. and W.,
500 ft. above branch.

Descend along steep E. slope.

80.00 Set a basalt stone, 18x12x7 ins., 12 ins. in the ground,
for cor. of secs. 1, 6, 7 and 12, marked with 5 grooves
on S., and 1 groove on N., from which

A Fir, 26 ins. diam., bears N. 30 *E., 15 lks. dist.,
mkd. T 33 S R 10 W S 6 B T.

A Fir, 18 ins. diam., bears S. 41 *E., 38 lks. dist.,
mkd, T 33 S R 10 W S 7 B T.

A Fir, 26 ins. diam., bears S. 54 *W., 21 lks. dist.,
mkd. T 33 S R 9 W S 12 B T.

A Fir, 24 ins. diam., bears N. $61\frac{1}{2}$ *W., 87 lks. dist.,
mkd. T 33 S R 9 W S 1 B T.

Land, mountainous.

Soil, stony, 4th rate.

Timber, Fir, and Pine.

Undergrowth, small Fir, Laurel, Chinquapin, Live Oak,