

Portion of East boundary of T. 33 S. R. 9 W.

CHAINS

Tan Oak and Rhododendron.

Mountainous land, or land covered with heavy timber and dense undergrowth exceptionally difficult to survey
80.00 chs.

North, between sec. 1 and 6.

Descend over steep mountainous land covered with heavy timber and dense undergrowth and exceptionally difficult to survey.

31.65 East fork of Kelsey Creek, 10 lks. wide, course W.,
1200 ft. below the sec. cor.

Ascend steep from Creek.

40.00 Set a sand stone, 18x9x8 ins., 12 ins. in the ground,
for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, from which

A Fir, 30 ins. diam., bears S.51*E., 30 lks. dist.,
mkd. $\frac{1}{4}$ S 6 B T.

A Fir, 30 ins. diam., bears S.40*W., 41 lks. dist.,
mkd. $\frac{1}{4}$ S 1 B T.

67.00 Top of spur, slopes W., 500 ft. above Creek.

Descend 300 Ft.

73.65 Branch, 2 lks. wide, course NW.

Across W. slope.

85.60 Intersect the Seventh Standard Parallel South, 18.04 chs.
West of the Standard cor. of Tp. 32 S., Rs 8 and 9 W.,
which is a post, firmly set, marked and witnessed as
described by the Surveyor General.

At the point of intersection,

Set a sand stone, 15x8x8 ins. 10 ins. in the ground, for
closing cor. to Tp. 33 S., Rs. 8 and 9 W., on E.
bdy. Tp. 33 S., R. 9 W., marked with 6 notches on N.
and S. edges, from which

A Fir, 10 ins. diam., bears S.78*E., 46 lks. dist.,
mkd. T 33 S R 8 W S 6 B T.

A Pine, 30 ins. diam., bears S.30*W., 29 lks. dist.,