

County Surveyor's Record, Douglas County, Oregon

Portion of East boundary of T. 33 S., R. 9 W.

CHAINS

mkd. T 33 S R 9 W S 1 B T.

Land, mountainous.

Soil, stony, 4th rate.

Timber, Fir, and Pine.

Undergrowth, small Fir, Laurel, Chinquapin, Oak, Rhododendron and Manzanita.

Mountainous land, or land covered with heavy timber and dense undergrowth exceptionally difficult to survey 103.64 chs. including 18.04 chs. connecting line.

October 23, 1909.

Resurvey of Portion of East Boundary of T. 33 S., R. 9 W. as surveyed by Norman D. Price, U.S. Surveyor, and Ira F. Shaffner, U.S. Transitman, under instructions dated Sept. 22, 1916.

North, on E. bdy. of sec. 24.*****

80.00

The cor. established for secs. 13, 18, 19 and 24, which is a slate stone, 9 x 8 x 6 ins. above ground, firmly set, mkd. and witnessed as described by the surveyor general.

Hereafter this cor. will refer to secs. 13 and 24 only. Obliterate markings on bearing trees referring to secs. E. of line.

North, on E. bdy of sec. 13.

2.53

Set a diorite stone, 20 x 8 x 8 ins., 15 ins. in the ground, for cor. of secs. 18 and 19, mkd. with 3 notches on N. and S. edges; from which

A Live Oak, 6 ins. diam., bears N.80 1/2°W., 10 lks. dist., mkd. T 33 S R 8 W S 18 B T.

A Fir, 40 ins. diam., bears S.50 1/2°E., 56 lks. dist., mkd. T 33 S R 8 W S 19 B T.

40.00

The 1/2 cor. established for secs. 13 and 18, which is a slate stone, 9 x 8 x 5 ins. above ground, firmly set, mkd. and witnessed as described by the surveyor general.