

Resurvey of Portion of East Boundary of T. 33 S., R. 9 W.

CHAINS

Hereafter this cor. will refer to sec. 13 only.

Obliterate markings on bearing tree referring to sec. 18 and take new bearing tree as follows:

A Fir, 18 ins. diam., bears S.40*W., 42 lks. dist.,
mkd. $\frac{1}{4}$ S 13 B T.

- 42.53 Set a sandstone, 15 x 8 x 8 ins., 10 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 18, mkd. $\frac{1}{4}$ on E. face ; from which
- A Fir, 20 ins. diam., bears N.50*E., 68 lks. dist.,
mkd. $\frac{1}{4}$ S 18 B T.
- A Fir, 24 ins. diam., bears S.70*E., 74 lks. dist.,
mkd. $\frac{1}{4}$ S 18 B T.

- 80.00 The cor. established for sec. 7, 12, 13 and 18, which is a sandstone, 10 x 5 x 5 ins., above ground, firmly set, mkd. and witnessed as described by the surveyor general.

Hereafter this cor. will refer to secs. 12 and 13 only.

Obliterate markings on bearing trees referring to secs. E. of line.

North, on E. bdy. of sec. 12.

- 2.53 Set a diorite stone, 15 x 10 x 8 ins., 10 ins. in the ground, for cor. of secs. 7 and 18, mkd. with 2 notches on N. and 4 notches on S. edge, from which
- A Fir, 11 ins. diam., bears N.22 $\frac{1}{2}$ *E., 67 lks. dist.,
mkd. T 33 S R 8 W S 7 B T.
- A Fir, 18 ins. diam., bears S.22*E., 65 lks. dist.,
mkd. T 33 S R 8 W S 18 B T.

- 40.00 The $\frac{1}{4}$ cor. established for secs. 7 and 12, which is a Fir post, 4 ins. sq., 12 ins. above ground, firmly set, mkd. and witnessed as described by the surveyor general.

Hereafter this cor. will refer to sec. 12 only.

Alongside of post,

Set a diorite stone, 12 x 10 x 8 ins., 8 ins. in the ground, mkd. $\frac{1}{4}$ on W. face.