

Resurvey of Portion of East Boundary of T. 33 S. R. 9 E.

CHAINS

Obliterate markings on bearing tree referring to sec. 7 and take new bearing tree as follows:

A Fir, 10 ins. diam., bears S.53\*W., 91 lks. dist., mkd. 1/4 S 12 B T.

42.53 Set a diorite stone, 15 x 10 x 6 ins., 10 ins. in the ground; for 1/4 cor. of sec. 7, mkd. 1/4 on E. face: from which

A Fir, 28 ins. diam., bears N.13\*E., 90 lks. dist., mkd. 1/4 S 7 B T.

A Pine, 40 ins. diam., bears S.1\*E., 88 lks. dist., mkd. 1/4 S 7 B T.

80.00 The cor. established for secs. 1, 6, 7 and 12, which is a diorite stone, 12x7x6 ins. , above ground, firmly set, mkd. and witnessed as described by the surveyor general.

Hereafter this cor. will refer to secs. 1 and 12 only.

Obliterate markings on bearing trees referring to sec. E. of line.

North, on E. bdy of sec. 1.

2.53 Set a diorite stone, 15 x 8 x 6 ins., 10 ins. in the ground, for cor. of secs. 6 and 7, mkd. with 1 notch on N. and 5 notches on S. edge, from which

A Fir, 18 ins. diam., bears N.7 1/2\*E., 12 lks. dist., mkd. T 33 S R 8 W S 6 B T.

A Fir, 14 ins. diam., bears S.37 1/2\*E., 36 lks. dist., mkd. T 33 S R 8 W S 7 B T.

40.00 The 1/4 cor established for secs. 1 and 6, which is a sandstone, 9 x 8 x 6 ins., above ground, firmly set, mkd. and witnessed as described by the surveyor general.

Hereafter this cor. will refer to sec. 1 only.

Obliterate markings on bearing tree referring to sec. 6 and take new bearing tree as follows:

A Madrona, 6 ins. diam., bears S.30\*W., 32 lks. dist.,