


Subdivisions of T. 33 S., R. 8 W.

CHAINS

- 4.15 Spur, slopes SW., desc. 15 ft. over NW. slope.
- 12.15 Ravine, course SW., asc. 475 ft. over SE. slope to spur.
- 21.30 Leave heavy timber, bears E. and W., continue through scattering timber.
- 29.30 Spur, slopes SW., desc. 65 ft. over NW. slope.
- 31.20 Ravine, course SW., asc. 165 ft. over SW. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor, with brass cap mkd.



from which

A Pine, 8 ins. diam., bears N.20*E., 312 lks. dist., mkd. $\frac{1}{4}$ S 12 B T.


A Fir, 24 ins. diam., bears N.76*W., 297 lks. dist., mkd. $\frac{1}{4}$ S 11 B T.

Asc. 205 ft. over SW. slope.

- 54.40 Ridge, bears E. and W.
- Trail, bears E. and W.
- Enter heavy timber, bears E. and W.
- Desc. 550 ft. over broken N. slope to sec. cor.

- 60.00 Trail, bears NE. and SW.
- Spring, bears N.75*E., 7.00 chs. dist.

- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 1, 2, 11 and 12, with brass cap mkd.



from which

A Fir, 8 ins. diam., bears N.35*E., 14 lks. dist., mkd. T 33 S R 8 W S 1 B T.

A Fir, 8 ins. diam., bears S.6 $\frac{1}{2}$ *E., 42 lks. dist., mkd. T 33 S R 8 W S 12 B T.

A Fir, 8 ins. diam., bears S.23 $\frac{1}{2}$ *W., 32 lks. dist., mkd. T 33 S R 8 W S 11 B T.