

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 33 S., R. 8 W.

CHAINS	*****
80.00	<p>N.0*1'. , between secs. 14 and 15.*****</p> <p>Set a diorite stone, 16 x 10 x 10 ins., 11 ins. in the ground, for cor. of secs. 10, 11, 14 and 15, mkd. with 4 notches on S. and 2 notches on E. edge, from which</p> <p>A Tan Oak, 6 ins. diam., bears S.88$\frac{1}{2}$*E., 36 lks. dist., mkd. T 33 S R 8 W S 14 B T.</p> <p>A Tan Oak, 10 ins. diam., bears N.37$\frac{1}{2}$*E., 8 lks. dist., mkd. T 33 S R 8 W S 11 B T.</p> <p>A Fir, 5 ins. diam., bears S.53$\frac{1}{2}$*W., 21 lks. dist., mkd. T 33 S R 8 W S 15 B T.</p> <p>A Fir, 32 ins. diam., bears N.42$\frac{3}{4}$*W., 63 lks. dist., mkd. T 33 S R 8 W S 10 B T.</p>
	<p>Land, mountainous.</p> <p>Soil, loose, coarse, rocky loam, 2nd and 3rd rate.</p> <p>Timber, Fir, Pine, Tan Oak, Cedar, Alder, Chinquapin and Madrona.</p> <p>Undergrowth, Sweet ^{Acorn} Acorn, Madrona and Snowbrush.</p>
40.00	<p>N.89*48'E., on random line between secs. 11 and 14.</p>
79.70	<p>Set temp. $\frac{1}{4}$ sec. cor.</p> <p>Intersect N. and S. line, 14 lks. N. of the cor. of secs. 11, 12, 13 and 14.</p>
	<p>Thence</p> <p>S.89*54'W., on a true line between secs. 11 and 14.</p> <p>Desc. 50 ft. over SW. slope, through heavy green timber and dense undergrowth.</p>
4.00	<p>Spur, slopes SW., desc. 230 ft. over NW. slope.</p>
11.60	<p>Branch, 2 lks. wide, course SW., asc. 80 ft. over SE. slope.</p>
28.00	<p>Spur, slopes S., desc. 430 ft. over SW. slope.</p>
39.70	<p>Branch, 2 lks. wide, course S., asc. 10 ft. over SE. slope</p>
39.85	<p>Set a diorite stone, 20 x 10 x 10 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face, from which</p>