

CHAINS											
8.30	Spur, slopes W., desc. 225 ft. over NW. slope.										
16.50	Spring branch, 1 lk. wide, course W., asc. 15 ft. over SW. slope.										
19.30	Spur, slopes W., desc. 170 ft. over NW. slope.										
26.40	Ravine, course W., asc. 90 ft. over SW. slope.										
30.90	Spur, slopes W., desc. 240 ft. over NW. slope.										
40.00	Set a limestone, 16 x 10 x 8 ins., 11 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, from which A Fir, 24 ins. diam., bears East, 2 lks. dist., mkd. $\frac{1}{4}$ S 10 B T. A Madrona, 20 ins. diam., bears N.79*W., 36 lks. dist., mkd. $\frac{1}{4}$ S 9 B T. Desc. 125 ft. over NW. slope.										
46.20	Branch, 2 lks. wide, course W., asc. 170 ft. over SW. slope.										
51.35	Spur, slopes W., desc. 40 ft. over NW. slope.										
58.00	Branch, 2 lks. wide, course SW., asc. 600 ft. over broken SE. slope to sec. cor.										
62.65	Leave heavy green timber, bears E. and W., continue through heavy standing dead timber.										
80.00	Head of ravine, course SE. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, with brass cap mkd.										
	<table border="1"> <tr> <td>T338</td> <td>R8W</td> </tr> <tr> <td>S4</td> <td>S3</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td>S9</td> <td>S10</td> </tr> <tr> <td colspan="2" style="text-align: center;">1919</td> </tr> </table>	T338	R8W	S4	S3	-----		S9	S10	1919	
T338	R8W										
S4	S3										

S9	S10										
1919											
	Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.										
	Land, mountainous.										
	Soil, loose, coarse, rocky loam, 3rd rate.										
	Timber, Fir, Pine, Live Oak and Madrona.										
	Undergrowth, Chinquapin, Lime Oak, and Madrona.										

N.89*52'E., on random line between secs. 3 and 10.