

Subdivisions of T. 33 S., R. 8 W.

CHAINS	
8.80	Ravine, course W., asc. 110 ft. over SW. slope.
20.70	Ridge, with trail along top, bears NW. and SE., desc. NE. slope.
36.40	Ravine, course NE., 365 ft. below ridge, asc. 45 ft. to
40.00	Spur, slopes NE.
	Set a limestone, 14 x 12 x 6 ins., 10 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, from which A Pine, 10 ins. diam., bears N.30*E., 23 lks. dist., mkd. $\frac{1}{4}$ S 3 B T. A Pine, 10 ins. diam., bears N.20*W., 4 lks. dist., mkd. $\frac{1}{4}$ S 4 B T.
	Desc. 85 ft. over NW. slope.
44.90	Ravine, course E., asc. 60 ft. over SE. slope.
49.85	Spur, slopes E., desc. 245 ft. over NE. slope.
57.10	Ravine, course NE., asc. 60 ft. over SE. slope.
62.00	Spur, slopes E., desc. 240 ft. over NE. slope.
84.58	Intersect the 7th St andard Parallel South, 9.63 chs, N.89*18'W., from the standard cor. fo secs. 33 and 34.
	At point of intersection,
	Set a diorite stone, 16 x 8 x 6 ins., 11 ins. in the ground, for closing cor. of secs. 3 and 4, mkd. C C on S., with 3 grooves on E. and W. faces, from which A Fir, 36 ins. diam., bears S.13*E., 60 lks. dist., mkd. T 33 S R 8 W S 3 C C B T. A Fir, 48 ins. diam., bears S.62*W., 62 lks. dist., mkd. T 33 S R 8 W S 4 C C B T.
	Land, mountainous.
	Soil, loose, coarse, rocky loam, 3rd rate.
	Timber, Pine, Fir, Madrona, Live Oak and Chinquapin.
	Undergrowth, Madrona, Buckhorn and Chinquapin.
	N.0*2'W., between secs. 16 and 17.*****
80.00	Set a diorite stone, 15 x 12 x 12 ins., 10 ins. in the ground, for cor. of secs. 8, 9, 16 and 17, mkd. with 4 notches on S. and E. edges, from which