

## Subdivisions of T. 33 S., R. 8 W.

## CHAINS

Land, mountainous.

Soil, loose, coarse, rocky loam, 3rd rate.

Timber, Fir, Pine, Live Oak, Madrona, Tan Oak, Cedar  
and Alder.

Undergrowth, Madrona, Live Oak, Chinquapin, Buckhorn  
and Manzanita.

N.0°2'W., on a true line between secs. 4 and 5.

Asc. 325 ft. over NE. slope, through heavy green timber  
and dense undergrowth.

21.00 Spur, slopes E., desc. 75 ft. over NE. slope.

27.70 Spring branch, 1 lk. wide, course E., asc. 210 ft. over  
S. slope.

35.80 Spur, slopes E., desc. 80 ft. over NE. slope.

40.00 Set a granite stone, 15 x 10 x 6 ins., 10 ins in the  
ground, for  $\frac{1}{4}$  sec. cor., mkd.  $\frac{1}{4}$  on W. face, from which  
A Fir, 14 ins. diam., bears N.40°E., 29 lks. dist.,  
mkd.  $\frac{1}{4}$  S 4 B T.  
A Fir, 14 ins. diam., bears West, 10 lks. dist.,  
mkd.  $\frac{1}{4}$  S 5 B T.

Desc. 110 ft. over NE. slope.

43.65 Ravine, course E., asc. 75 ft. over SE. slope.

46.65 Spur, slopes E., desc. 20 ft. over NE. slope.

48.60 Spring branch, 1 lk. wide, course SE., asc. 470 ft. over  
SW. slope.

64.55 Spur, slopes SE., desc. 55 ft. over NE. slope.

67.55 Ravine, course SE., asc. 120 ft. over SW. slope.

73.60 Ridge, bears E. and W.

Trail, bears E. and W.

Desc. 235 ft. over broken NW. slope.

83.94 Intersect the 7th Standard Parallel South, 13.93, chs.,  
West from the standard cor. of secs. 32 and 33.

At point of intersection,

Set a porphyry stone, 16 x 10 x 8 ins., 11 ins. in the  
ground, for closing cor. of secs. 4 and 5, mkd. C C