

County Surveyor's Record, Douglas County, Oregon

9899

South Boundary of T. 24 S., R. 1 E., W. M., as surveyed by Alonzo Gesner, Deputy Surveyor, under Contract No. 659 dated May 21, 1896.

CHAINS

I began on the Willamette Meridian at Tp. Cor. to Tps. 24 and 25 S., which is a Pine post, $4\frac{1}{2}$ ins. sq., $2\frac{1}{2}$ ft. above ground, firmly set and marked T 24 S S 31 on NE., R 1 E S 6 on SE., T 25 S S 1 on SW., and R 1 W S 36 on NW. faces, with 6 notches on the N., E., S., and W. edges, from which

A Cedar, 12 ins. diam., bears N.64*E., 17 lks. dist., marked T 24 S R 1 E S 31 B T.

A Fir, 24 ins. diam., bears S.37*E., 66 lks. dist., marked T 25 S R 1 E S 6 B T.

A Fir, 24 ins. diam., bears S.86*W., 50 lks. dist., marked T 25 S R 1 W S 1 B T.

A Fir, 12 ins. diam., bears N.25*W., 47 lks. dist., marked T 24 S R 1 W S 36 B T.

I have described the corner as I found it.

Thence I run

East, on a true line, on the South Bdy. of Sec. 31.

Var. 20*E.

1.75 Creek, 2 lks. wide, course N.
Ascend.

24.51 A Fir, 24 ins. diam. A line tree marked with 2 notches on the E. and W. sides.

35.75 Top of ridge, course N. and S.
Descend.

37.92 Set basalt stone, 14x8x5 ins., 12 ins. in the ground, on steep hillside, sloping NE., for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on the N. side, from which

A Silver Fir, 18 ins. diam., bears S.10*W., 19 lks. dist., marked $\frac{1}{4}$ S B T.

A Silver Fir, 10 ins. diam., bears N.30*W., 10 lks. dist., marked $\frac{1}{4}$ S B T.

51.00 Creek, 3 lks. wide, course N.

77.92 Set basalt stone, 18x16x8 ins., 12 ins. in the ground, on steep hillside sloping West for cor. to Secs. 31, 32, 5 and 6.

+1200

-200