

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 24 S., R. 1 E

CHAINS 5.75	Creek, 2 lks. wide, course S. Ascend.	-50
23.00	Creek, 2 lks. wide, course SW. Continue to ascend.	
35.50	A quartz ledge.	
37.50	Top of rocky ridge, course NE. and SW. Pass over cone.	+600
40.00	Set basalt stone, 20x10x4 ins., 15 ins. in the ground, on hillside, sloping South, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. side, from which A Fir, 10 ins. diam., bears S.45*30'E., 4 lks. dist., marked $\frac{1}{4}$ S B T. A Madrone, 7 ins. diam., bears N.33*E., 18 lks. dist., marked $\frac{1}{4}$ S B T.	
58.00	Top of spur, sloping SW. Pass over cone.	
69.00	Point of rock projecting South.	
74.25	Top of ridge, course SE. and NW.	
80.00	Set basalt stone, 12x10x5 ins., 7 ins. in the ground, on side hill, sloping N., for cor. to Secs. 1, 2, 35 and 36, marked with 5 notches on the West and 1 notch on the E. sides, from which A Fir, 10 ins. diam., bears N.46 ^{46'} *30'E., 25 lks. dist., marked T 24 S R 1 E S 36 B T. A Fir, 10 ins. diam., bears S.54*30'E., 30 lks. dist., marked T 25 S R 1 E S 1 B T. A Fir, 10 ins. diam., bears S.79*W., 59 lks. dist., marked T 25 S R 1 E S 2 B T. A Fir, 20 ins. diam., bears N.22*30'W., 110 lks. dist., marked T 24 S R 1 E S 35 B T.	
	Land, mountainous. 80.00 chs. Soil, 2nd and 3rd rate. Heavily timbered with Fir. 80.00 chs. Undergrowth, Fir, Vine Maple and Mountainbalm.	

REC: LARRY HUGGARD
BLM. P.L.S. 6/1979