

County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey
of the Willamette Meridian, through T. 25 S.

CHAINS

to the 1/4 sec. cor. is N.0*07'W., 32.62 chs., and of
the north half mile is N.0*14'W., 40.20 chs.

Thence

North, from the sec. cor., retracing bet. secs. 1 and 6.

40.48 Fall 37 lks. E. of the 1/4 sec. cor.

80.74 Fall 65 lks. E. of the cor. of Tps. 24 and 25 S., Rs.
1 E. and 1 W.

The bearing and length of the south half mile is
N.0*32'W., 40.48 chs., and of the north half mile is
N.0*24'W., 40.26 chs.

Resurvey

The cor. established for Tps. 25 and 26 S., Rs. 1 E. and
1 W., is a basalt stone, 18x12x8 ins., loosely set in
a mound of stone, marked with 6 notches on N., E., S.,
and W. edges.

I now change this cor. to refer to Tps. 25 S., Rs. 1 E.
and 1 W. only.

Re-set the basalt stone, 14 ins. in the ground, marked

25S on N.,
1E on E., and
1W on W. face; from which

A fir, 60 ins. diam., bears S.36*E., 72 lks. dist.,
old B.T., the marks on which I now destroy.

A fir, 18 ins. diam., bears S.11 1/2*W., 50 lks. dist.
old B.T., the marks on which I now destroy.

A fir, 30 ins. diam., bears N.54 1/2*W., 80 lks.
dist., marked T 25 S R 1 W S 36 B T. (old B.T.)

A fir, 8 ins. diam., bears N.67 1/2*E., 86 lks.
dist., marked T 25 S R 1 E S 31 B T. (New B.T.)

The old bearing tree in T. 25 S., R. 1 E., is dead
and fallen.

Thence

N.1*07'E., on a true line, resurveying E. bdy. of sec. 36.
Desc. 175 ft. over NE. slope, through heavy timber and