


County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey of the Willamette Meridian, through T. 25 S.

CHAINS

- 0.60 Right bank of Canton Creek, course S.15*E.
- 2.60 Left bank of Canton Creek; asc. 150 ft. over SW. slope.
- 5.65 Canton Creek Trail, and Forest Service Telephone line, bears NW. and SE.
- 17.50 Bluff, 75 ft. high, facing W., bears E., 1 ch. dist. Thence along W. slope.
- 22.50 Desc. 85 ft. over NW. slope.
- 27.10 Brook, 1 lk. wide, course S.80*W.
- 29.75 Creek, 1 lk. wide, course W.; asc. 70 ft. over SW. slope.
- 38.90 Brook, 1 lk. wide, course SW.
- 39.40 Point of intersection of line bet. secs. 30 and 31, determined as hereinafter set forth.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for closing cor. of secs. 30 and 31, with brass cap marked



from which

A fir, 12 ins. diam., bears N.13*E., 27 lks. dist., marked T 25 S R 1 E S 30 C C B T.

A fir, 10 ins. diam., bears S.64*E., 63 lks. dist., marked T 25 S R 1 E S 31 C C B T.

- 40.69 The old cor. established for secs. 25, 30, 31 and 36, which is a badly decayed post, with marks illegible; from which:

A fir, 12 ins. diam., bears N.51*E., 36 lks. dist., marked T 25 S R 1 E S 30 B T. (old B.T.)

A fir, 12 ins. diam., bears S.78*E., 20 lks. dist., marked T 25 S R 1 E S 31 B T. (old B.T.)

A fir, 30 ins. diam., bears S.14*W., 66 lks. dist., old B.T. with marks burned out.

A pine, 14 ins. diam., bears S.70*W., 70 lks.