

Retracement and Dependent Resurvey  
of the Willamette Meridian, through T. 25 S.

CHAINS

dist., marked T 25 S R 1 W S 36 B T. (new B.T.)  
A fir, 36 ins. diam., bears N.23\*W., 51 lks.  
dist., marked T 25 S R 1 W S 25 B T. (old B.T.)  
I now change this cor. to refer to secs. 25 and 36 only,  
and destroy the marks on the bearing trees in secs.  
30 and 31.

In place of the decayed post  
Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in  
the ground, for cor. of secs. 25 and 36 only, with  
brass cap marked

T25S	T25S
S25	R 1 E
S36	S30
R1W	1927

Land, mountainous.  
Soil, coarse sandy loam; 2nd and 3rd rate.  
Timber, fir, hemlock, pine, cedar, yew and alder.  
Undergrowth, vine maple, rhododendron, hazel, yew  
and alder.

Thence

N.0\*58'E., on a true line, on E. bdy. of sec. 25.  
Asc. 137 ft. over SW. slope, through heavy timber and  
dense undergrowth.

- 2.60 Continue asc. along W. slope.
- 15.00 Desc. 65 ft. over NW. slope.
- 19.35 Creek, 1 lk. wide, course SW.; asc. 475 ft. over SE.  
slope.
- 22.00 Continue asc. over S. slope.
- 25.00 Continue asc. over SW. slope.
- 38.60 Mid point bet. closing cors., determined as hereinafter  
set forth.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in  
the ground, for  $\frac{1}{4}$  sec. cor. of sec. 30 only, with  
brass cap marked