

14
County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey
of the Willamette Meridian, through T. 25 S.

CHAINS	
	$\frac{1}{4}$ S30 1927
	from which
	A fir, 6 ins. diam., bears N.24 $\frac{1}{2}$ *E., 20 lks. dist., marked $\frac{1}{4}$ S 30 B T. A pine, 6 ins. diam., bears S.41*E., 5 lks. dist., marked $\frac{1}{4}$ S 30 B T.
40.49	The $\frac{1}{4}$ sec. cor. established for secs. 25 and 30, which is a basalt stone, 12x10x8 ins., loosely set in the ground, marked $\frac{1}{4}$ on W. face; from which A fir, 14 ins. diam., bears S.85*E., 45 lks. dist., old B.T. the marks on which I now destroy. A fir, 36 ins. diam., bears S.60*W., 31 lks. dist., old B.T. with marks grown over. I now change this cor. to refer to sec. 25 only. Alongside the stone Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked <div style="text-align: center; margin: 10px 0;"> $\frac{1}{4}$ S25 1927 </div> from which A fir, 6 ins. diam., bears N.65*W., 52 lks. dist., marked $\frac{1}{4}$ S 25 B T.
	Thence N.0*22'E. Desc. 115 ft. over NW. slope.
5.00	Dry ravine, course W.
10.95	Creek, 1 lk. wide, course SW.; asc. 640 ft. over SE. slope.
37.99	Point of intersection of line bet. secs. 19 and 30, determined as hereinafter set forth. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for closing cor. of secs. 19 and 30, with brass cap marked