

Retracement and Dependent Resurvey
of the Willamette Meridian, through T.25 S.

CHAINS

Thence

N.0°34'E., on a true line, on E. bdy. of sec. 24.

Asc. 45 ft. over SE. slope, through heavy timber and dense undergrowth.

5.50 Spur, slopes W.; desc. 800 ft. over steep N. slope.

17.00 Continue desc. along W. slope.

26.70 Rocky spur, slopes NW.; continue desc. over N. slope.

30.20 Creek, 5 lks. wide, course W.; asc. 225 ft. over bluffs on SW. slope.

37.52 Mid point bet. closing cors., determined as hereinafter set forth.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 19 only, with brass cap marked

|
 $\frac{1}{4}$ S19
 1927

from which

A fir, 30 ins. diam., bears N.86°E., 118 lks. dist., marked $\frac{1}{4}$ S 19 B T.A fir, 24 ins. diam., bears S.72°E., 120 lks. dist., marked $\frac{1}{4}$ S 19 B T.

★ - - - - This cor. is at the foot of bluff, 75 ft. high, facing W.

39.53 The $\frac{1}{4}$ sec. cor. established for secs. 19 and 24, which is a basalt stone, 12x12x8 ins., loosely set, marked $\frac{1}{4}$ on W. face; from which

A madrona, 16 ins. diam., bears N.53°E., 12 lks. dist., old B.T., the marks on which I now destroy.

The old B.T. in sec. 24 is dead and fallen.

I now change this cor. to refer to sec. 24 only.

Alongside the stone

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

★ - The Brass Cap for this corner is at the foot of the bluff, but the BT's are on top of the 75 ft. Bluff. (This information furnished by B. Lecklider, 12/30/58.)